



DOI: [10.71317/jgst.2.9.2026.536](https://doi.org/10.71317/jgst.2.9.2026.536)

Journal of Global Social Transformation

Journal homepage: <https://rjsaonline.org/index.php/JGST>



Smart Parking Management and the Integration of Artificial Intelligence into Urban Policy Planning

Soneha¹, Muhammad Adil Amin², Umm E Habiba³, Nishwa Jamshed⁴, Muhammad Zaryab Tasawar⁵, Faizan Arif⁶

¹ University of Engineering and Technology, Lahore

Email: sonehanadeem786@gmail.com

² University of Engineering and Technology, Lahore

Email: muhammadadil5858@gmail.com

³ University of Engineering and Technology, Lahore

Email: ummehabiba310uh@gmail.com

⁴ University of Engineering and Technology, Lahore

Email: nishwajamshed@gmail.com

⁵ University of Engineering and Technology, Lahore

Email: zaryabmustafa922@gmail.com

⁶ University of Engineering and Technology, Lahore

Email: faizan_arif17@outlook.com

ARTICLE INFO

Submission:

July 05, 2026

Revised:

July 23, 2026

Accepted:

August 24, 2026

Available Online:

September 04, 2026

Keywords:

Smart Parking Systems; Artificial Intelligence; Urban Policy Planning; Dynamic Pricing; Digital Twins; SFpark; EU AI Act; Sustainable Mobility; IoT; Performance-Based Management

Corresponding author:

Soneha

Email:

sonehanadeem786@gmail.com

ABSTRACT

The rapid urbanization and motorization of global cities have rendered traditional static parking management frameworks increasingly inadequate, contributing to traffic congestion, economic inefficiency, and environmental degradation. This comprehensive review examines the paradigm shift from conventional parking systems to Artificial Intelligence-driven Smart Parking Systems (SPS) and their integration into urban policy planning. The paper systematically analyzes the technical architecture of SPS, encompassing multi-tiered sensor networks including inductive loops, magnetometers, computer vision, and millimeter-wave radar alongside communication protocols such as LoRaWAN and 5G networks. A critical examination of dynamic performance-based pricing mechanisms, grounded in behavioral economics and Pigouvian principles, demonstrates how maintaining 60-80% occupancy rates effectively eliminates cruising traffic. Empirical evidence from the SFpark pilot project reveals significant outcomes: 31% improvement in target occupancy achievement, 12% reduction in parking search times, and 30% decrease in daily greenhouse gas emissions. The review further explores AI's transformative role in urban policy through Digital Twin frameworks and generative analytics, enabling predictive spatial modeling and evidence-based curb-space reallocation. Legal and ethical dimensions are addressed through the European Union's AI Act framework, establishing risk-based governance tiers for public-space AI deployment. Despite technical challenges including sensor reliability and data security, emerging solutions such as blockchain integration and Vehicle-to-Everything communications present promising pathways. This review concludes that AI-enabled smart parking represents a critical component of sustainable urban mobility, offering municipalities data-driven tools to optimize spatial resources while balancing efficiency gains with privacy protections and social equity considerations.

Introduction

Accelerating global urbanization and motorization have made urban curb space one of the most contestable and mismanaged assets in modern civil infrastructure. Traditional parking frameworks, reliant on fixed-rate pricing structures and manual enforcement, are ill-equipped to address dynamic urban travel demands. This imbalance generates extensive traffic congestion, economic inefficiency, and environmental degradation (Millard-Ball et al., 2021). Empirical transportation studies demonstrate that drivers searching for parking commonly termed "cruising" account for 30% to 50% of total peak-period traffic in dense urban centers, with average search times ranging between 3.5 and 14 minutes per trip. This unnecessary circulation exacerbates vehicle miles traveled (VMT), fuel consumption, local air pollution, and carbon emissions (Pierce & Shoup, 2013).


The transition from static parking management to AI-driven Smart Parking Systems (SPS) represents a paradigm shift in urban transportation policy. Historical parking interventions evolved from basic mechanical meters introduced in the 1930s to electronic meters in the 1980s, and eventually to early sensor-based detection networks at the turn of the 21st century (Geng & Cassandras, 2012). Today, the integration of Artificial Intelligence (AI), the Internet of Things (IoT), edge computing, and real-time predictive analytics allows municipal authorities to transform parking from a static spatial allocation challenge into a dynamic, demand-responsive mobility network. Reflecting this technical transition, the global market for smart parking systems is projected to expand from USD 5.3 billion in 2022 to USD 21 billion by 2030, representing a robust compound annual growth rate (CAGR) of 18.47% (Lee et al., 2022).

Integrating AI into smart parking management bridges municipal operational technology and overarching urban policy. Beyond easing localized parking searches, AI-enabled SPS platforms generate granular spatio-temporal datasets. When fed into urban planning engines, these data streams inform zoning reforms, public transit alignment, emission-reduction strategies, and digital twin modeling. However, deploying these ubiquitous sensing networks within public spaces introduces regulatory, technical, and ethical complexities. Modern urban policy planning must balance the efficiency gains of real-time spatial optimization against stringent data privacy regulations, such as the European Union's Artificial Intelligence Act (AI-Turjman & Malekloo, 2019).

Technical Architecture and Data Sensing Ecosystems

Smart Parking Systems operate on a multi-tiered architecture comprising hardware sensing modalities, networking middleware, edge-cloud compute environments, and algorithmic inference engines. Synthesizing real-time physical space occupancy into actionable urban planning intelligence requires robustness across every tier of this technical stack (Marsden, 2006).

Figure 1: Architectural Workflow and Data Processing Pipeline of an M2M-Enabled Intelligent Urban Mobility Ecosystem for Dynamic Parking and Access Control



Sensor Hardware and Perception Layers

At the physical perception layer, vehicle detection relies on an array of intrusive and non-intrusive sensor technologies. Intrusive sensors, such as Inductive Loop Detectors (ILD) and in-ground Magnetometers, offer direct physical vehicle detection. Magnetometers measure localized distortions in the Earth's magnetic field caused by the ferrous mass of an entering vehicle. While highly accurate and energy-efficient, in-ground sensors require road surface cutting, making them vulnerable to street degradation and costly to maintain (Arnott & Inci, 2006).

Non-intrusive sensors are mounted on existing urban infrastructure, such as streetlights, buildings, or utility poles. These include Ultrasonic sensors, Infrared detectors, Radar (Radio Detection and Ranging), Photoelectric sensors, and AI-enabled Video Cameras operating via Computer Vision (CV) algorithms. Optical camera systems leverage deep convolutional neural networks (CNNs) to monitor broad vehicle zones simultaneously, enabling multi-space tracking and automated license plate recognition (ALPR) (Shoup, 2006).

However, optical systems struggle with environmental line-of-sight obstructions, lens contamination, and extreme weather conditions like rain, fog, or snow. To overcome these single-source limitations, modern SPS deploy integrated sensor fusion frameworks. Combining high-frequency radar which penetrates adverse weather with optical vision sensors managed by AI fusion models produces superior spatial detection accuracy across variable urban environments (Lin et al., 2017).

Network Topologies, Edge Computing, and Middleware Integration

Data collected at the perception layer must be transmitted efficiently to centralized or distributed computing platforms. Modern deployments utilize diverse wireless protocols tailored to specific latency, range, and power requirements, including 5G cellular networks, Long Range Wide Area Networks (LoRaWAN), ZigBee, Dedicated Short-Range Communications (DSRC), and Wi-Fi (Fahim et al., 2021).

To mitigate bandwidth congestion and transmission latency, smart city architectures increasingly deploy edge computing nodes directly adjacent to physical sensor arrays. Edge nodes run compressed computer vision and anomaly-detection models locally, processing raw video or radar telemetry on-site and transmitting only lightweight metadata such as binary occupancy states or anonymized timestamps to central servers. This pipeline routes raw visual or telemetry signals through local feature extraction at the edge, converting heavy data streams into compact metadata before reaching centralized AI analytical engines (Bibri & Krogstie, 2020).

At the city-wide platform level, open-source middleware architecture manages high-volume concurrent IoT telemetry streams. A notable operational example is the Sentilo platform deployed in the Les Corts district of Barcelona. Monitoring over 500 street spaces, Sentilo standardizes multi-sensor data streams and dramatically reduces network latency. Traditional smart parking software suffered from signal transmission lags across wireless networks, causing app users to navigate toward spaces that had already been occupied. Sentilo compresses this transmission latency to a few seconds, preserving data integrity for navigation applications and municipal traffic control platforms (Lymperis & Goumopoulos, 2023).

Table 1: Comparative Analysis of Sensor Modalities and Communication Protocols in Smart Parking Infrastructures

Sensing / Category	Networking	Technology Modality	Operational Mechanism	Primary Strengths	Technical Limitations & Challenges
Intrusive Sensing	Physical	Inductive Loop Detectors (ILD)	Electromagnetic field changes induced by metal vehicle mass	Exceptionally high vehicle presence detection accuracy	High installation costs; road surface damage; susceptible to roadwork wear
Intrusive Sensing	Physical	Wireless Magnetometers	Measurement of Earth's magnetic field distortions	Low power consumption; multi-year battery life; hidden profile	Subject to structural electromagnetic interference; costly pavement retrofits
Non-Intrusive Sensing	Spatial	Computer Vision / CCTV	CNN-based image segmentation and object classification	Multi-space monitoring; ALPR capacity; utilizes existing poles	Weather sensitivity; line-of-sight occlusion; strict privacy constraints

Non-Intrusive Sensing	Spatial	Millimeter-Wave Radar	High-frequency electromagnetic echo reflection analysis	Unaffected by weather, light, or environmental conditions	Higher hardware costs; complex spatial calibration requirements
Wireless Protocols		LoRaWAN	Sub-GHz long-range low-power radio communication	Wide coverage radius; low power draw; ideal for simple status bits	Extremely low payload bandwidth; higher latency than cellular networks
Wireless Protocols		5G Cellular Networks	High-frequency multi-band cellular infrastructure	Ultra-low latency; massive data bandwidth; supports dense streams	High subscription overhead; elevated operational power consumption

Dynamic Pricing Mechanisms and Behavioral Economics

Transforming physical parking sensors into an active management system relies on dynamic, performance-based pricing models. Grounded in Pigouvian land-use economics and street-parking pricing theories established by Donald Shoup and William Vickrey, dynamic parking management aims to optimize space utilization rather than maximize municipal revenue (Mackowski et al., 2015).

The Performance-Based Pricing Framework

The economic goal of performance-based curb management is to maintain a target occupancy rate of 60% to 80% on every street block face. Achieving this target ensures that one to two parking spots remain vacant per block face at any given time. Maintaining this operational buffer virtually eliminates cruising traffic, allowing drivers to park immediately near their destination (Tsai et al., 2025).

Under a performance-based framework, pricing adjustments follow a clear logic based on observed block occupancy:

- When block occupancy falls below 30%, hourly rates are lowered significantly (e.g., reduced by \$0.50) to encourage utilization.
- When occupancy ranges between 30% and 60%, hourly rates are lowered moderately (e.g., reduced by \$0.25).
- When occupancy falls within the 60% to 80% target window, pricing remains unchanged.
- When block occupancy exceeds 80%, indicating over-crowding, hourly rates are increased (e.g., raised by \$0.25) to nudge long-term parkers toward off-street facilities or alternative transportation modes.

When parking rates are set too low, demand spikes to 100% occupancy. Drivers then cycle through congested blocks seeking open spots, generating external costs in wasted time, excess fuel burn, and heightened street risk. Conversely, excessively high prices leave parking spaces underutilized, harming adjacent commercial businesses, depressing localized employment, and shifting parking pressure into neighboring residential zones (Ulvi et al., 2026).

Dynamic pricing algorithms evaluate historical occupancy patterns alongside real-time data inputs including weather conditions, local urban events, transit schedules, and time of day to automatically adjust meter rates. The responsiveness of parking demand to these price adjustments is defined by the price elasticity of demand (ε), expressed mathematically as:

$$\varepsilon = \frac{\% \Delta \text{ Occupancy Rate}}{\% \Delta \text{ Parking Price}}$$

Across empirical urban transportation studies, the overall price elasticity of demand for curb parking averages approximately -0.4 , indicating an inelastic yet actionable consumer response. Elasticity varies significantly depending on location density, time of day, trip purpose, and local public transit availability (Sutjarittham et al., 2020).

Empirical Insights: The SFpark Pilot Evaluation

The most comprehensive empirical demonstration of demand-responsive parking pricing is the federally funded SFpark project in San Francisco. Managed by the San Francisco Municipal Transportation Agency (SFMTA) and supported by an USD 18 million grant from the United States Department of Transportation's Value Pricing Pilot Program, SFpark instrumented seven pilot zones with street sensors and smart meters, keeping designated control areas for comparative evaluation (Pierce et al., 2015).

Instead of applying rapid real-time rate oscillations which confuse drivers SFpark implemented systematic rate adjustments approximately every six to eight weeks across 10 distinct rate adjustment cycles. Rate shifts followed a transparent, occupancy-driven rule set:

- Occupancy **80% – 100%**: Hourly rate increased by \$0.25.
- Occupancy **60% – 80%** (Target Zone): Hourly rate remained unchanged.
- Occupancy **30% – 60%**: Hourly rate decreased by \$0.25.
- Occupancy **< 30%**: Hourly rate decreased by \$0.50.

Floors and Ceilings: Rates were bounded between a minimum of \$0.25/hr and a maximum of \$6.00/hr (Krishnamurthy & Ngo, 2020).

The empirical results of the two-year evaluation period revealed significant improvements in traffic management and urban efficiency:

- **Target Occupancy Convergence:** Time spent within the optimal 60%–80% target occupancy window grew by 31% in pilot areas, compared to a modest 6% increase in control zones. In areas with high payment compliance, target occupancy achievement increased by nearly 95%.
- **Mitigation of Over-Occupancy:** The duration during which street blocks were overcrowded (90% – 100% occupancy) dropped by 16% in pilot areas (and 45% in high-compliance pilot zones), whereas control areas saw a 51% increase in over-occupancy (Demisch, 2016).
- **Reduction in Cruising Time and Distance:** Difference-in-difference spatial regression models revealed that SFpark reduced average parking search times by 12% and search distances by 10% relative to control areas.
- **Environmental Impact:** Daily greenhouse gas (GHG) emissions generated by drivers searching for parking in pilot areas fell by 30% (from 7.0 to 4.9 metric tons per day), compared to a minor 6% reduction in control zones (Ngo & Krishnamurth, 2017).
- **Net Rate and Revenue Dynamics:** Counter to public perception that performance pricing serves as a revenue tax, the average on-street meter rate dropped by 4% (falling 11 cents from \$2.69 to \$2.58/hr). Concurrently, average rates in municipal garages dropped by 42 cents (from \$3.45 to \$3.03/hr). Higher charges on overcrowded blocks were offset by rate cuts on underutilized streets.
- **Transit Mode Substitution:** Micro-level data merging meter pricing with transit bus ridership showed that peak-period meter rate increases correlated with a statistically significant rise in local bus ridership, demonstrating direct mode-substitution away from private driving when curb parking costs reflect true land value (Mohassel, 2017).

Table 2: Empirical Performance Metrics of SFpark Demand-Responsive Pricing Deployment


Analytical Category	Specific Performance Index		Baseline (Pre-SFpark)	State	Post-Implementation State	Net Systemic Impact
Occupancy Metrics	Target Achievement	Range (60-80%)	Low stability	target	31% relative increase in target frequency	Stable open spaces; eliminated localized block saturation
Occupancy Metrics	Over-Occupancy Duration (>90%)		High congestion	chronic	16% overall drop (45% in high compliance blocks)	Block overcrowding reduced vs. +51% control area increase
Cruising Metrics	Average Search Time	Parking	High search time	baseline	12% net search time reduction	Direct driver time savings; diminished urban street friction
Cruising Metrics	Average Distance Travelled	Search	High dedicated search	VMT to	10% net search distance reduction	Lower neighborhood VMT; reduced street intersection wear

Environmental Metrics	Daily Parking Search GHG Emissions	7.0 metric tons / day	4.9 metric tons / day	30% direct reduction in daily emissions (vs. 6% control)
Economic Metrics	Average On-Street Hourly Meter Rate	\$2.69 / hour	\$2.58 / hour	\$0.11 average rate reduction; disproved tax inflation fears
Economic Metrics	Off-Street Garage Hourly Rate	\$3.45 / hour	\$3.03 / hour	\$0.42 average rate reduction; redirected long-term stays off-street

AI Integration in Urban Policy, Spatial Planning, and Digital Twins

As artificial intelligence systems mature beyond real-time occupancy updates, their primary value shifts toward predictive urban policy planning and dynamic spatial modeling. Municipalities are increasingly leveraging deep learning models, Generative AI, and spatial Digital Twins (DT) to simulate mobility policies before physical deployment (Bittencourt et al., 2026).

Figure 2: Technological Core Domains and Enabling Interdisciplinary Ecosystem of Next-Generation Parking 4.0 Systems.



Digital Twin Frameworks and Generative Analytics

A Digital Twin represents a real-time virtual counterpart of a city's physical transportation network. By integrating distributed data streams from smart parking meters, license plate cameras, enforcement logs, weather APIs, and public transit schedules, digital twins model the complex relationships governing urban spatial demand. This continuous feedback loop processes live urban inputs into a virtual simulation engine, enabling city managers to evaluate structural policy changes dynamically (Kirwan & Zhiyong, 2020).

A notable deployment is the Digital Twin framework developed for the city of Caserta, Italy. The Caserta framework integrates IoT sensor feeds with predictive machine learning models and Generative AI modules:

- **Predictive Analytics:** Forecasting localized spatial parking demand hours or days in advance using historical occupancy, local calendars, and meteorological data.
- **Generative Scenario Testing:** Utilizing Generative AI models to construct synthetic, real-world "what-if" mobility scenarios. Planners simulate how reallocating curb spaces to delivery zones, altering parking meter locations, or shifting pricing boundaries affects city-wide traffic equilibrium without disrupting physical traffic flow.
- **Enforcement and Compliance Spatial Optimization:** Predictive spatial modeling guides municipal parking enforcement officers along optimized routing paths based on real-time violation probabilities, improving compliance while lowering fuel use (Lartey & Law, 2025).

Curb-Space Reallocation, Housing Policy, and Equity

Integrating AI into urban policy challenges long-standing planning practices, particularly minimum parking mandates in municipal building codes. Traditionally, urban policies forced residential and commercial developments to supply fixed ratios of off-street parking spaces. Empirical studies show these requirements significantly inflate housing costs; for instance, a landmark San Francisco study demonstrated that off-street parking mandates added USD 47,000 to the construction cost of single-family housing units, raising the qualifying annual buyer income by over USD 9,000 (Cao et al., 2026).

By providing accurate, continuous data on true parking demand, AI platforms allow planners to replace arbitrary minimum parking requirements with flexible, performance-based spatial strategies. Surplus parking spaces can be repurposed into parklets, bus lanes, micro-mobility charging hubs, or expanded pedestrian areas (Żywiołek et al., 2026).

Simultaneously, planners must evaluate the socio-economic equity impacts of smart parking policies. Equity-focused pricing research shows that lower-income drivers depend heavily on street parking due to reduced access to private off-street garages. However, empirical analyses from SFpark demonstrate that demand-responsive pricing does not systematically sort drivers across blocks by income level. Lower-income parkers proved less price-sensitive than expected, benefiting disproportionately from reduced search times and cleaner local air (Shokry, 2026).

In specialized environments, such as large medical centers or municipal complexes, advanced allocation algorithms prioritize accessibility over purely economic rationing. For example, fast grouping-permutation heuristics allocate premier parking spots based on the total passenger count within arriving vehicles rather than vehicle count alone, maximizing access for higher-occupancy vehicles (Turoń, 2025).

Legal Frameworks, Governance, and Ethics: The EU AI Act Paradigm

Deploying automated sensing and AI inference across public streetscapes introduces significant legal, governance, and civil liberty challenges. The installation of vision-based networks capable of visual tracking, behavioral monitoring, and automated license plate scanning conflicts with privacy rights if left unregulated. The European Union's Artificial Intelligence Act (Regulation (EU) 2024/1689) establishes a comprehensive, risk-based regulatory framework governing public space AI technologies (Ganz Resende, 2025).

Risk Tier Categorization in Smart City Mobility

The EU AI Act classifies artificial intelligence applications into distinct risk tiers, imposing stringent compliance requirements as potential harms to fundamental rights increase:

Prohibited AI Systems (Article 5)

Technologies deemed unacceptable threats to civil liberties are strictly banned, subject to narrow law enforcement exceptions. In urban smart parking contexts, prohibited systems include:

- Real-time Remote Biometric Identification (RBI) (e.g., automated facial recognition or gait tracking deployed across public CCTV parking feeds).
- Untargeted visual scraping of public camera feeds to construct facial recognition databases.
- Cognitive behavioral manipulation or automated social scoring systems deployed within public spaces (Almada & Petit, 2025).

Consequently, camera-based smart parking deployments must strictly restrict automated detection models to vehicle boundaries, license plates (under defined statutory frameworks), and spatial occupancy states, explicitly excluding human biometric tracking (Ebers et al., 2021).

High-Risk AI Systems (Article 6 & Annex III)

AI platforms governing critical public infrastructure including municipal traffic management, emergency response routing, and public surveillance analytics are designated as High-Risk. Smart parking systems tied directly to real-time traffic signal adjustments or predictive law enforcement routing fall under high-risk governance mandates. High-risk deployments require:

- Rigorous pre-market Fundamental Rights Impact Assessments (FRIA).
- End-to-end technical logs, data provenance tracking, and risk management compliance shields.
- Human-in-the-loop oversight mechanisms, ensuring human operators retain ultimate authority over automated enforcement or dynamic pricing adjustments (Mintoo et al., 2022).

Low-Risk / Transparency-Only Systems

AI systems designed strictly for utility optimization such as ultrasonic or radar-based vehicle detection that does not gather personal identifiable information (PII) fall into lower risk tiers. These systems require basic operational transparency under Article 50, obligating city authorities to notify citizens when AI systems process spatial data within public spaces (Zdravković et al., 2025).

Table 3: Risk Tier Classification and Governance Mandates under the EU AI Act for Urban Mobility Technologies

EU AI Act Risk Tier	Technology Scope in Smart Cities	Statutory Legal Status	Mandatory Obligations	Regulatory	Operational Compliance Requirements
Prohibited Risk (Article 5)	Real-time facial/gait recognition via smart parking cameras; public social scoring	Prohibited (Strictly forbidden in public spaces)	Absolute prohibition subject to narrow judicial law enforcement exemptions		Strip facial biometric extraction modules from edge-computing vision nodes
High Risk (Article 6 & Annex III)	Traffic management systems; predictive enforcement; ex-post biometric tracking	Permitted under strict conditions	Fundamental Rights Impact Assessments (FRIA); technical logging; human oversight		Implement human-in-the-loop decision checkpoints; maintain complete audit trails
Transparency Risk (Article 50)	Non-biometric occupancy platforms; automated pricing chatbots; generic AI UI	Permitted with notice	Public disclosure and transparent operational notices		Display prominent public signage; publish system capabilities and data boundaries
Minimal Risk	Ultrasonic/magnetic slot sensors; basic non-PII vehicle counting algorithms	Permitted without specific restrictions	Adherence to general cybersecurity and software safety standards		Maintain basic network encryption, secure data transmission, and standard maintenance

Challenges, Emerging Horizons, and Future Outlook

Despite rapid technical advances, large-scale deployment of AI-driven smart parking systems faces significant technical and operational hurdles (Olmos Medina et al., 2025).

Hardware and Communication Bottlenecks

Physical sensor arrays remain vulnerable to harsh weather conditions, physical wear, and battery degradation. Optical vision systems suffer from line-of-sight occlusions caused by large commercial delivery vehicles, trees, or temporary construction. To improve field reliability, future infrastructure planning must prioritize multi-sensor fusion architectures combining optical vision, radar, and edge-AI analytical modules (Pierce & Shoup, 2013).

At the network layer, traditional centralized star topologies introduce single-point-of-failure risks where a single gateway outage disables an entire sub-network. Transitioning to decentralized wireless mesh network architectures ensures that if an individual communication node fails, neighborhood network telemetry automatically re-routes through adjacent nodes, preserving communication integrity (Ulvi et al., 2026).

Data Integrity, Security, and Decentralized Ledgers

Smart parking management platforms aggregate extensive spatial mobility data. Security vulnerabilities in parking software could allow malicious actors to manipulate price signals, falsify occupancy status, or track the location of individual vehicles (Krishnamurthy & Ngo, 2020).

Integrating Immutable Distributed Ledgers (Blockchain technology) into data management frameworks offers a cryptographic defense. Decentralized ledgers ensure data integrity across multi-tenant municipal databases, prevent unauthorized manipulation of transaction logs, and secure automated machine-to-machine micropayments between autonomous vehicles and smart meters (Sutjarittham et al., 2020).

Autonomous Vehicles and Vehicle-to-Everything (V2X) Communications

The emergence of autonomous vehicle (AV) fleets will fundamentally redefine smart parking management. Instead of relying on mobile driver interfaces, smart parking platforms will interface directly with vehicle software via Vehicle-to-Everything (V2X) protocols (Bittencourt et al., 2026).

Autonomous vehicles will communicate with municipal AI systems to negotiate, reserve, and pay for optimal drop-off, staging, and parking slots based on real-time pricing and battery charging requirements. This shift will transform static curb space into an automated, software-managed logistics layer (Fahim et al., 2021).

Conclusion

This comprehensive review establishes that the integration of Artificial Intelligence into smart parking management represents a transformative paradigm shift in urban transportation policy and spatial planning. The transition from static, fixed-rate parking frameworks to dynamic, AI-driven systems has demonstrated measurable improvements across multiple dimensions of urban efficiency and sustainability. The technical architecture of modern SPS encompassing multi-modal sensor fusion, edge computing, and decentralized communication networks provides the foundational infrastructure for real-time occupancy monitoring and predictive analytics. The economic evidence, particularly from the SFpark pilot project, conclusively demonstrates that performance-based pricing mechanisms effectively optimize curb space utilization while reducing cruising time, vehicle miles traveled, and environmental emissions. The 30% reduction in daily greenhouse gas emissions and 12% decrease in parking search times underscore the tangible benefits of data-driven parking management. Beyond operational efficiency, AI integration enables sophisticated urban policy planning through Digital Twin frameworks and generative analytics, allowing municipalities to simulate mobility interventions before physical deployment. The legal and ethical governance frameworks, exemplified by the EU AI Act, provide necessary safeguards to balance technological innovation with fundamental rights protections. Looking forward, emerging technologies including autonomous vehicles, Vehicle-to-Everything communications, and blockchain-based data security will further revolutionize curb-space management. However, successful implementation requires addressing persistent challenges including sensor reliability, data privacy, and social equity considerations. The evidence collectively suggests that AI-enabled smart parking systems, when thoughtfully designed and equitably implemented, constitute an essential component of sustainable, resilient, and intelligent urban mobility ecosystems for twenty-first-century cities.

References

1. Almada, M., & Petit, N. (2025). The EU AI Act: Between the rock of product safety and the hard place of fundamental rights. *Common market law review*, 62(1).
2. Al-Turjman, F., & Malekloo, A. (2019). Smart parking in IoT-enabled cities: A survey. *Sustainable Cities and Society*, 49, 101608. <https://doi.org/10.1016/j.scs.2019.101608>
3. Arnott, R., & Inci, E. (2006). An integrated model of downtown parking and traffic congestion. *Journal of Urban Economics*, 60(3), 418–442. <https://doi.org/10.1016/j.jue.2006.04.004>
4. Bibri, S. E., & Krogstie, J. (2020). The emerging data-driven smart city and its innovative applied solutions for sustainability: The cases of Singapore and Barcelona. *Energy Informatics*, 3, 1–42. <https://doi.org/10.1186/s42162-020-00114-0>
5. Bittencourt, J. C. N., Flores, T. K., Jesus, T. C., & Costa, D. G. (2026). On the role of AI in building generative urban intelligence. *Artificial Intelligence Review*, 59(2), 78.
6. Cao, H., King, D., Wang, X., Malarkkan, A. V., Liu, K., Wang, D., & Fu, Y. (2026). Parking Without Building: Agentic AI for Parking Planning Through Urban Contradiction Reasoning. Preprints 05- 1-18
7. Demisch, A. (2016). Demand-responsive pricing on the cheap: Estimating parking occupancy with meter payment data. *Transportation Research Record*, 2543(1), 125-133.
8. Ebers, M., Hoch, V. R., Rosenkranz, F., Ruschemeier, H., & Steinrötter, B. (2021). The European Commission’s proposal for an Artificial Intelligence Act a critical assessment by members of the Robotics and AI Law Society (RAILS). *J*, 4(4), 589-603.
9. Fahim, A., Hasan, M., & Chowdhury, M. A. (2021). Smart parking systems: Comprehensive review based on various aspects. *Heliyon*, 7(5), e07050. <https://doi.org/10.1016/j.heliyon.2021.e07050>
10. Ganz Resende, F. (2025). *From policy to practice: AI integration in Brazilian and German public administration* (Doctoral dissertation, Universität Potsdam).
11. Geng, Y., & Cassandras, C. G. (2012). A new “smart parking” system based on optimal resource allocation and reservations. *IEEE Transactions on Intelligent Transportation Systems*, 14(3), 1129–1139. <https://doi.org/10.1109/TITS.2013.2252428>
12. Kirwan, C., & Zhiyong, F. (2020). *Smart cities and artificial intelligence: convergent systems for planning, design, and operations*. Elsevier.
13. Krishnamurthy, C. K. B., & Ngo, N. S. (2020). The effects of smart-parking on transit and traffic: Evidence from SFpark. *Journal of Environmental Economics and Management*, 99, 102273.
14. Lartey, D., & Law, K. M. (2025). Artificial intelligence adoption in urban planning governance: A systematic review of advancements in decision-making, and policy making. *Landscape and Urban Planning*, 258, 105337.
15. Lee, C. P., Leng, F. T. J., Habeeb, R. A. A., Amanullah, M. A., & Rehman, M. H. ur. (2022). Edge computing-enabled secure and energy-efficient smart parking: A review. *Microprocessors and Microsystems*, 93, 104612. <https://doi.org/10.1016/j.micpro.2022.104612>
16. Lin, T., Rivano, H., & Le Mouël, F. (2017). A survey of smart parking solutions. *IEEE Transactions on Intelligent Transportation Systems*, 18(12), 3229–3253. <https://doi.org/10.1109/TITS.2017.2685143>
17. Lymperis, D., & Goumopoulos, C. (2023). Sedia: A platform for semantically enriched IOT data integration and development of Smart City Applications. *Future Internet*, 15(8), 276.
18. Mackowski, D., Bai, Y., & Ouyang, Y. (2015). Parking space management via dynamic performance-based pricing. *Transportation Research Procedia*, 7, 170-191.

19. Marsden, G. (2006). The evidence base for parking policy A review. *Transport Policy*, 13(6), 447-457. <https://doi.org/10.1016/j.tranpol.2006.05.009>
20. Millard-Ball, A., Hampshire, R. C., & Weinberger, R. (2021). The unavoidable congestion of curbside parking. *Journal of the American Planning Association*, 87(1), 58-71. <https://doi.org/10.1080/01944363.2020.1814210>
21. Mintoo, A. A., Saimon, A. S. M., Bakhsh, M. M., & Akter, M. (2022). National resilience through AI-driven data analytics and cybersecurity for real-time crisis response and infrastructure protection. *American Journal of Scholarly Research and Innovation*, 1(01), 137-169.
22. Mohassel, A. (2017). Drivers' Response to Temporal and Spatial Parking Price Adjustment: Evidence from SFpark Project. American Institutes for Research, 06, 200-217
23. Ngo, N. S., & Krishnamurth, C. K. (2017). The effects of demand-responsive parking on transit usage and congestion: Evidence from SFpark. *Pdxscholar* 03, 119-128
24. Olmos Medina, J. S., Maradey Lázaro, J. G., Rassölkin, A., & González Acuña, H. (2025). An overview of autonomous parking systems: Strategies, challenges, and future directions. *Sensors*, 25(14), 4328.
25. Pierce, G., & Shoup, D. (2013). Getting the prices right: An evaluation of pricing schemes for residential parking permits. *Journal of the American Planning Association*, 79(1), 16-25. <https://doi.org/10.1080/01944363.2013.787307>
26. Pierce, G., Willson, H., & Shoup, D. (2015). Optimizing the use of public garages: Pricing parking by demand. *Transport Policy*, 44, 89-95.
27. Shokry, R. (2026). Reframing Urban Intelligence: A Critical Global Analysis of Artificial Intelligence Integration in Inclusive and Sustainable Urban Design. *JES. Journal of Engineering Sciences*, 54(4), 535-556.
28. Shoup, D. C. (2006). Cruising for parking. *Transport Policy*, 13(6), 479-486. <https://doi.org/10.1016/j.tranpol.2006.05.005>
29. Sutjarittham, T., Gharakheili, H. H., Kanhere, S. S., & Sivaraman, V. (2020). Monetizing parking IoT data via demand prediction and optimal space sharing. *IEEE Internet of Things Journal*, 9(8), 5629-5644.
30. Tsai, W. H., Chen, H. C., Lee, K. H., & Yang, C. F. (2025). Implementation of an AIoT-based Smart Parking System for Urban Mobility and Sustainable Infrastructure Management. *Sensors & Materials*, 37(9, Part 3), 4267.
31. Turoń, K. (2025). Sustainable urban mobility transitions From policy uncertainty to the CalmMobility paradigm. *Smart Cities*, 8(5), 164.
32. Ulvi, H., Arslan Selçuk, S., & Satoğlu, G. (2026). Smart Parking Systems as Data-Oriented Architectural Spaces: A Conceptual Framework for Sustainable Urban Mobility. *Sustainability*, 18(7), 3229.
33. Zdravković, S., Dobrić, F., Injac, Z., Lukić-Vujadinović, V., Veličković, M., Bursać Vranješ, B., & Marinković, S. (2025). AI-Driven Safety Evaluation in Public Transport: A Case Study from Belgrade's Closed Transit Systems. *Sustainability*, 17(18), 8283.
34. Żywiołek, J., Ejdyś, J., Wolniak, R., & Bećirović, S. (2026). *Urban Transformation Through Artificial Intelligence: Management Innovations for Sustainable Development*. Taylor & Francis.



2026 by the authors; Journal of Global Social Transformation (JGST). This is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC-BY) license (<http://creativecommons.org/licenses/by/4.0/>).