DOI: https://doi.org/10.71317/kjard.2.5.2026.527

The Kashmir Journal of Academic Research and Development

Journal homepage: https://rjsaonline.org/index.php/KJARD

Research on Energy Crisis in Pakistan and Alternative Energy Assets

Faraz Khan
Department of Computer Science & IT, Sir Syed University of Engineering and Technology
Email: fakhan@ssuet.edu.pk

Ramla Jamil
Department of Civil Engineering, NED University of Engineering and Technology
Email: imramlajamil@gmail.com

Muhammad Hamid
Department of Computer Science & IT, Sir Syed University of Engineering and Technology
Email: hamidrajput450@gmail.com

ARTICLE INFO

Received:
March 28, 2026
Revised:
April 10, 2026
Accepted:
April 25, 2026
Available Online:
May 11, 2026

Keywords:
power assets, sustainable source of energy, GDP and population, economics friendly energy.

Corresponding Author:
FarazKhan
Email: : fakhan@ssuet.edu.pk

ABSTRACT

The unending energy crisis in Pakistan enlightened the need to increase the installed capacity of electrical power system. Fossil fuels are broadly utilized in machinery as fuel because of its large calorific content, accessibility, power generation & transportation, but its reservoirs are depleting daily. The current situation of power sector in Pakistan needs to work on renewable or sustainable source of energy. Fuel from biomass is a promising alternative energy asset which can be resolve the present fuel starvation issue to the considerable level.

Introduction

Decreasing fossil powers assets, are a major risk to the world's economy. It causes is behind the foremost basic financial, natural and formative issues confronting the world nowadays. Not a single Millennium Development Goals (MDGs) will be achieved in the absence of crucial advancement in the energy sector.

The fundamental & basic law between energy demand and Gross Domestic Product (GDP) remains robust, i.e., more people with more money means more energy will be generated and used. It is undeniable that Pakistan's energy consumption has increased in tandem with the country's GDP and population.

Globally, energy policies have been established with the goal of achieving alternate energy provision. Anaerobic digestion can be an effective method for treating bio-waste, not only in terms of reducing environmental impact, but also in terms of producing renewable biogas electricity. The conversion of biomass to methane can be divided into two types: thermal and biological conversion. Alessandro Volta, an Italian scientist, was the first to notice that flammable air was being produced in

lakes and ponds. In France, further scientific research has begun with the goal of reducing or eliminating the foul odour created by waste water pools.

In 1923, biogas was sold to the general public for the first time in Germany. Until the Second World War, the only people who used agricultural products to make bio-gas on a big basis were Germans. Gobar Gas is the name given to biogas produced by small-scale digestion systems in Pakistan. 90% of the wood produced in the country is utilised as fuel. Every year, about 7000 acres of land in Pakistan gets reforested.

Objectives

- We examine the possibility of using biomass produced by cattle as a source of renewable energy to meet fractional energy demands.
- We concentrate on evaluating locally manufactured biogas-powered generators to determine their electrical execution capability when using filtered fuel.

Methodology

Bio-Digester

Bio-Digester is a type of material. For this project, the materials were chosen based on the feed material, the type of gas to be made, and how easy and available they were. Mild Steel sheets were used to make the material.

Type of Bio-Digester

➢ **Classification On The Basis of Design**

On the basis of feed stock input and output operation, biogas digester is divided into two types:

1. Batch Type Digester

Batch plant is completely filled with a portion of feedstock, which is emptied completely after a fixed period of time. The digester is fed with a new feedstock and the process is repeated. Operation cost of batch type digester is low but maintenance cost is high. Normally batch type digesters are employed for dry digestion.

2. Continuous Type Digester


In a continuous type plant, feedstock is added all the time, usually once a day. Continuous digesters produce biogas without stopping to load new feedstock or unload digested effluent like batch digesters do. Biogas is always and always will be made. There are three kinds of continuous digesters.

- Horizontal tank system
- Vertical tank system
- Multiple tanks system

➢ **Classification On The Basis Of Gas Collection**


1. Fixed Dome Digester

This digester has a fixed, non-movable dome. The reaction chamber and compensation tank make up this sort of reactor. Difference when digester gas is produced between reaction chamber slurry level and compensating tank. Due to the gas's continuous pressure slurry surface volume. Most digesters are dome-type. Underground to protect digester contents. Subterranean Installation reduces day-to-night temperature swings.



2. Floating Dome Digester

It comprises of a Toro spherical or spherical or cylindrical dome-shaped top used for gas collection and transport. When pressure builds inside the reactor, the dome rises to maintain constant pressure and falls as gas is consumed. The dome can contact the slurry inside or via the vessel's water jacket. The one with a water jacket has reduced leakage chances and may move easily regardless of digester viscosity. During rector construction, internal/external guiding frames should be used to prevent the dome from tilting.



Result

Cow waste of almost 60 kg together with slime water 60 Liters is blended together beneath mesophilic conditions. Using an advanced PH metre, the pH of the slime water was discovered to be 7.4, whereas that of the slurry was 8.5. Within the reactor, the inoculums condition has been established. The methanogens have been given a pressure-driven maintenance time (HRT) of about 10 to 15 days. The combustibility test is carried out on the fifth day. The gas did not ignite, but the coordinate adhere's fire dissipated quickly, indicating the presence of CO_2. We deduced that the reactor is in the acidogenesis stage at this point. Every day, the digester's contents are physically blended with an initiator at a speed of 4 rev/min, since excellent blending can result in increased microorganism passage rates. On day 10, the combustibility is tested once more, and this time it is found to be satisfactory.

As soon as the mesospheric parameter is fulfilled on day 15, we add about 60 kilogram's of garbage to 60 litres of slime water, with the PH maintained at the same level as previously. The arch began to rise to accommodate the trapped gas within the reactor; at this point, it is estimated that the arch has climbed nearly 5 to 7 inches in size. The upper arch reaches its maximum height on the 20th day.

The filtration unit was checked, and the 0.7 KVA gas generator that was linked to it was operational. It was discovered that electrical efficiency was improved by 10%. Unfortunately, the entire unit was left out in the open, where it was exposed to the scorching sun rays, and the plastic bottle was melted down as a result of the high exothermic chemical reaction in the NaOH chamber, posing a barrier to further chemical cleaning. We created a water scrubbing unit due to a lack of time, which is simpler and less expensive than chemical cleaning. A practical experiment was conducted, and it worked perfectly. Furthermore, because the gas testing equipment at PCSIR laboratory was not in working order, we were unable to determine the filtered gas output.

Conclusion

Renewable energy technology holds great potentials as alternatives to conventional energy to reduce the local electricity deficit. Biogas is considered as a promising renewable energy source to supply local electricity deficit. Recently, the biogas plants based on cattle excrement gained much attention in view of the availability of huge amounts of cattle excrement. Present project reports the amount of cattle waste produced and its feasibility for electrical generation.

In Pakistan, a large amount of waste is produced each year, and cow or buffalo waste is currently not used in any meaningful way. The creation of biogas through anaerobic digestion is one of the most promising methods for utilizing this waste. This energy disposition might be initiated by a combination of researchers, entrepreneurs, venture capitalists, and government initiatives.

References

Anonymous. (2009). Organic waste types for biogas production. Available: http://www.biogas-renewable-energy.info/waste_nature.html

M. Ragazzi, M. P. Maniscalco, V. Torretta, N. Ferronato, and E. Rada, Anaerobic digestion as sustainable source of energy: A dynamic approach for improving the recovery of organic waste vol. 119, 2017.

A. A. Ibrahim, L. Kuburi, Siyaka, M. Balogun, K. Muhammad Usman, and A. Aliu Biogas Production from Cow Dung and Kitchen Waste for Heat Energy Applications, 2016.

P. Pandey and M. Soupir, Impacts of Temperatures on Biogas Production in Dairy Manure Anaerobic Digestion vol. 4, 2012.

A. Saleh, Comparison among different models of biogas plants, 2015.

2026 by the authors; Journal of The *Kashmir Journal of Academic Research and Development*. This is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC-BY) license (http://creativecommons.org/licenses/by/4.0/).